


DATA SHEET | ENGLISH




DIMENSION DRAWING



ELECTRICAL CONNECTION


Version 1xPNP with Poti

Pin	Assignment
1	Ub+
3	0 V
4	Out 1
2	NC



Version 2xPNP with IO-Link

Pin	Assignment
1	Ub+
3	0 V
4	Out 1 / IO-Link
2	Out 2



General data

Display	LED green: Operating display
	LED yellow: Switching points OUT 1 / 2
Setting options	1xPNP: Switching point via potentiometer
	2xPNP: Different parameters via IO-Link, e.g.:
	Switching points; NO/NC; Hysteresis / Window mode;
	Switching delay
Operating medium	Filtered, dry or oiled air and non-corrosive gases
Protection class	IP40 / IP68

Ordering information

Process connection	Pressure range
hose connection $\varnothing 1/8''$	O/R
hose connection $\varnothing 5/32''$	14
hose connection $\varnothing 1/4''$	18
hose connection $\varnothing 5/16''$	15
hose connection $\varnothing 3/8''$	19
Protection class	
IP40	5
IP68	8
Output	
1x PNP / NO	11
1x PNP / NC	12
2x PNP with IO-Link	33

Mechanical data

Material housing	Plastic PBT/PC
Process connection	Push-in 4/6/8/10 mm
Mounting position	Any
Weight	approx. 20 g (4/6mm)
	approx. 30 g (8/10mm)

Electrical data

Electrical connection	M8x1 4-pole
Operating voltage	9...30 VDC
Current consumption	< 25 mA
Short-circuit / reverse polarity protection	yes / yes

Output (Version 1xPNP with potentiometer)

Output signal	1x PNP
Max. output current	max. 100 mA
Output voltage	approx. Ub -1.5 V
Output function	NO/NC (fixed setting)
Switching point	Adjustment potentiometer 5-100%
Switching hysteresis	approx. 5% FS
Repeatability	$\pm 3\%$ FS

Output (Version 2xPNP with IO-Link)

Output	2x PNP + IO-Link
Output voltage	approx. Ub -1.5 V
Max. output current	max. 200 mA per output
Output function	NO/NC (programmable)
Accuracy (23°C)	$\pm 0.5\%$ FS
max. temperature error	$\pm 1.5\%$ FS (-25°C...85°C)
Repeatability	$\pm 0.2\%$ FS
Long term drift	$\leq 0.1\%$ / a
IO-Link specification	Version 1.1
Transmission rate	COM 2 / 38,4 kBit/s

Pressure range

Measuring range	(bar)	(psi)	0...0.25	-1...0	-1...1	-1...3	-1...10	0...10	0...12
			0...3.26	-14.5...0	-14.5...14.5	-14.5...43.5	-14.5...145	0...145	0...174
max. overpressure*	(bar)	(psi)	0.5	2	6	15			
			7.25	29	87	217.6			

Operating conditions

Operating temperature	Operation: -25°...+85°C
EMC / interference immunity	EN61000-6-2
EMC / interference emission	EN61000-6-4

*overpressure not continuously allowed